

VPL-EX130

3LCD portable projector with 3000 ANSI lumens



VPL-EX130 - 3LCD portable projector with 3000 ANSI lumens



The VPL-EX130 projector has been designed to be both simple to use and to deliver high picture quality and brightness. This model incorporates Sony's innovative BrightEra technology which produces higher brightness, colour accuracy and increased reliability. It has a Colour Light Output of 3000 lumens and a contrast of 700:1. This level of brightness, coupled with excellent picture quality in XGA (1024 x 768) resolution, allows users to deliver bright and colourful presentations in a variety of lighting conditions.

Weighing approximately 3.1kg, the new stylish, practical design of this projector includes a built-in tilt angle of 8° that automatically produces perfectly proportioned images. Height adjustment and controls are simple to use and easy to access making the VPL-EX130 an ideal projector for professional presentations in schools, universities and corporate environments.

This product comes with PrimeSupport – fast, hassle-free repairs and a helpline offering expert technical advice. Which gives you the peace of mind that Sony is looking after your equipment, and your business.

Features

3LCD BrightEra technology

This innovative inorganic panel technology was designed by Sony to deliver improved panel light resistance, higher brightness, higher resolution and increased panel reliability.

Built-in optical shift

A built-in 8° tilt angle gives a perfectly proportioned presentation on the screen or wall.

Dynamic Detail Enhancer

Generates high quality images through the Interlace/Progressive conversion processor, resulting in extremely accurate image reproduction.

Digital Zoom (4x)

Magnify a portion of the image displayed by 4x.

Ceiling Mountable

For permanent applications.

Image Freeze Function

Freeze the image displayed and make changes to your presentation without the audience knowing.

Benefits

Colour Light Output 3000 lumens

Colour Light Output is a metric that measures a projector's ability to deliver colour.

Short-throw projection

Achieve a pin sharp 80-inch image (diagonal) from just 2.4 metres away making it ideal for presenting in small meeting rooms and classrooms.

Security Features

Password access, control panel lock and optional security cable and security bar can all help to prevent misuse, tampering and theft in classrooms or meeting rooms

2 x Power-saving modes

Lamp Cutoff: Lamp cuts off if no signal is input for 10 minutes and lights again when a signal is input or any key is pressed.

Standby: The projector goes into standby mode if no

signal is input for 10 minutes and power consumption reduced to less than 3W.

Off and Go

The projector is ready to be unplugged as soon as it is switched off. There is no need to wait for the fan to turn off.

Easy to use

The projector's height adjuster is located at the back to make it easier to see the effects of moving it upon your projected image and the control panel is located on the top of the projector.

Technical Specifications

Optical	
Projector System	0.63 inch TFT LCD panel, (BrightEra)
Projector Lens	Approx. 1.2 times zoom lens (manual), f=18.53 to 22.18mm, F=1.65 to 1.93
Throw Distance	80" to 300" (Screen 2.4 to 2.7m)
Lamp	210W Ultra high pressure lamp
LampLife	3000 H (Lamp mode: High) / 5000 h (lamp mode: Standard)
Screen Coverage	40" to 300" (40" to 300" auto focus operation range)
Light Output	3000 (Lamp mode: High) / 2000 (Lamp mode: Standard)
ColourLight Output	3000 (Lamp mode: High) / 2000 (Lamp mode: Standard)
Contrast	700:1
Colour System	NTSC3.58/PAL/SECAM/NTSC4.43/PAL-M/PAL-N/PAL60 system

Signals	
Resolution	750 horizontal TV lines (Video input)
Acceptable Computer Signal	fH: 19 to 92 kHz / fV: 48 to 92 Hz Maximum input signal resolution: SXGA+ (fV: 60 Hz)
Acceptable Video Signal	Composite video, Y/C video, 15 k RGB 50/60 Hz, Progressive component 50/60, Hz, DTV (480/60I, 480/60P, 575/50i, 575/50P, 720/50P, 720/ 60P, 1080/50i, 1080/ 60i)
Keystone Correction	(Vertical) Max. +/- 30° Degrees (Auto)

General	
Dimensions (WxHxD)	314 × 114 × 269 mm (w/h/d) (without projecting parts)
Mass	Approx. 3.1 kg (6 lb 13 oz)
Cabinet Colour	White
Power Requirements	AC 100 to 240 V, 2.7 to 1.1 A, 50/60 Hz

Power Consumption	Max.: 260W, in Standby: 3W Standard / 1W Low
Heat Dissipation	912 BTU
Fan Noise	31dB (Lamp mode: Standard)
Speaker	Monaural speaker system, Approx. 40x28.5mm (output 1W MAX)
Operating Temperature	0 to 40°C degrees (32 to 104°F degrees)
Operating Humidity	35 to 85% (no condensation)
Storage Temperature	-20 to 60°C degrees (-4 to 140°F Degrees)
Storage Humidity	10 to 90%
OSD Languages	English, Dutch, French, Italian, German, Spanish, Portuguese, Russian, Swedish, Norwegian, Japanese, Chinese (Simplified / Traditional), Korean, Thai, Arabic, Turkish, Polish and Vietnamese

Safety Regulations	
Safety Regulations	UL60950-1 2nd Edition, cUL (CSA No.60950-1 2nd Edition), FCC Class B , IC Class B , CE (LVD: EN60950-1 2nd Edition (FIMKO), EMC), C-Tick, NOM, SASO, PSB, VCCI, JEITA, eK (K60950 + EMC)

Interfaces	
Video Inputs	S Video: Y/C Mini DIN 4 pin x 1
Input A	RGB / Component: HD D-sub15-pin, female Analogue RGB/component
Input B	RGB / Component: HD D-sub15-pin, female Analogue RGB/component
Output	RGB: Analogue RGB : HD D-sub 15-pin (female)
Remote	RS232: D-sub 9-pin (female)

Supplied Accessories	
Remote Commander RM-PJ6 (1)	

Lithium Battery for Remote Commander CR2025 (1)	
HD D-sub 15-pin cable (1.8m) (1)	
Security Label	
CD-ROM (Operating Instructions)	

Quick Reference Manual	
Safety Regulations	
AC Power Cord	
Lens Cap	
Warranty Card (outside of box)	
Replacement Lamp	LMP-E210

Accessories

Warranty and Support Agreements



PrimeSupport Plus FPJ2E

An optional service offering that extends the duration of the included PrimeSupport cover by 2 years - achieving a total of 5 years' cover.



PrimeSupport Plus FPJL

If the projector lamp fails, this optional service offering provides one free replacement lamp during the 3 years of PrimeSupport cover.



PrimeSupport Plus FPJ2EU

An optional service offering extending duration of included PrimeSupport cover by 2 years - achieving a total of 5 years' peace of mind. Also includes next business day delivery of loan unit.



PrimeSupport Plus FPJU

An optional service offering that provides a free next-business-day loan unit throughout the 3 years of PrimeSupport cover.